

Safety Data Sheet: NC-123 PLUS AEROSOL

Supersedes Date 07/21/2010

Issuing Date 08/01/2013

1. PRODUCT AND COMPANY IDENTIFICATION

Product Name NC-123 PLUS AEROSOL
Recommended use Lubricant Clear coating
Information on Manufacturer
CHEMSEARCH DIV. OF NCH CORP.
BOX 152170
IRVING, TX 75015

Product Code 5625
Chemical nature Petroleum distillates
Emergency Telephone Number

Telephone inquiry
972-579-2477

2. HAZARD IDENTIFICATION

Color Amber

Physical State Liquid

Odor Solvent

GHS

Classification

Physical Hazards

Flammable aerosols
Gases under pressure

Category 2
Compressed Gas

Health Hazard

Aspiration Toxicity
Acute Dermal Toxicity
Acute Inhalation Toxicity - Gas
Acute Inhalation Toxicity - Dusts and Mists
Skin Corrosion/Irritation
Serious Eye Damage/Eye Irritation
Specific target organ systemic toxicity (single exposure)
Specific target organ systemic toxicity (repeated exposure)

Category 1
Category 4
Category 3
Category 4
Category 2
Category 2B
Category 3
Category 2

Other hazards

None

Labeling

Signal Word

DANGER



Hazard Statements

H223 - Flammable aerosol
H331 - Toxic if inhaled
H336 - May cause drowsiness or dizziness
H312 - Harmful in contact with skin
H315 - Causes skin irritation
H320 - Causes eye irritation
H304 - May be fatal if swallowed and enters airways
H373 - May cause damage to organs through prolonged or repeated exposure
H280 - Contains gas under pressure; may explode if heated

Precautionary Statements

P210 - Keep away from heat, sparks, open flames or hot surfaces.
P211 - Do not spray on an open flame or other ignition source
P251 - Pressurized container: Do not pierce or burn, even after use
P280 - Wear protective gloves, protective clothing and eye protection.
P260 - Do not breathe vapor, mist or gas
P271 - Use in a well-ventilated area.
P270 - Do not eat, drink or smoke when using this product
P264 - Wash face, hands and any exposed skin thoroughly after handling.
P304 + P340 - IF INHALED: Remove person to fresh air and keep at rest in a position comfortable for breathing.
P312 - Call a physician if unwell.
P302+ P352 - IF ON SKIN: Wash with plenty of soap and water
P332 + P313 - If skin irritation occurs, get medical attention.
P362 - Take off contaminated clothing and wash before reuse
P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P337 + P313 - If eye irritation persists, get medical attention.
P301+ P330 + P331 - IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. Call a physician if unwell.
P410 + P412 - Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F
P403 - Store in a well-ventilated place
P501 - Dispose of contents and container in accordance with applicable regulations.

25 % of the mixture consists of ingredient(s) of unknown toxicity

3. COMPOSITION / INFORMATION ON INGREDIENTS

Component	CAS-No	Weight %
Petroleum distillates, hydrotreated light	64742-47-8	10-30
Solvent naphtha (petroleum), medium aliphatic	64742-88-7	10-30
Petroleum distillate	8052-41-3	10-30
Propane	74-98-6	7-13
Mineral oil	8012-95-1	1-5
Butane	106-97-8	1-5
Nonane	111-84-2	1-5
Barium sulfonate	61790-48-5	1-5
Paraffin wax	8002-74-2	1-5

4. FIRST AID MEASURES

General advice	Avoid contact with skin, eyes and clothing. Avoid breathing vapors, mist, or gas.
Eye Contact	Rinse thoroughly with plenty of water, also under the eyelids. Get medical attention if irritation develops and persists.
Skin Contact	Wash off with soap and plenty of water. Get medical attention if irritation develops and persists.
Inhalation	If inhaled, remove to fresh air. Get medical attention if symptoms occur.
Ingestion	Drink 1 or 2 glasses of water. Do NOT induce vomiting. Get medical attention immediately. Never give anything by mouth to an unconscious person.
Notes to physician	Aspiration hazard if swallowed - can enter lungs and cause damage. May be fatal if swallowed and enters airways.

5. FIRE-FIGHTING MEASURES

Flash Point	106 °F / 41 °C	Method	Seta closed cup
Flammability Limits in Air %		Upper	9.5
Suitable Extinguishing Media		Lower	0.8
Water spray. Foam. Dry chemical. Carbon dioxide (CO ₂). Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.			
Specific hazards arising from the chemical			
Extremely flammable. Solvent vapors are heavier than air and may spread along floors. Flame extension: 24 inches / 61 cm and Burnback: 4 inch / 10 cm.			
Protective Equipment and Precautions for Firefighters			
As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.			
Aerosol Level (NFPA 30B) -	3		
NFPA	Health 2	Flammability 4	Instability 0
HMIS	Health 2	Flammability 4	Instability 0

6. ACCIDENTAL RELEASE MEASURES

Personal Precautions	Use personal protective equipment. Remove all sources of ignition. Ensure adequate ventilation. Prevent further leakage or spillage if safe to do so. Material can create slippery conditions.
Environmental Precautions	Do not flush into surface water or sanitary sewer system.
Methods for Containment	Contain spillage, soak up with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and transfer to a container for disposal according to local / national regulations (see section 13).
Methods for Cleaning Up	Use clean non-sparking tools to collect absorbed material. Pick up and transfer to properly labeled containers.
Neutralizing Agent	Not applicable.

7. HANDLING AND STORAGE

Handling	Keep away from open flames, hot surfaces and sources of ignition. Take precautionary measures against static discharges. Avoid contact with skin, eyes and clothing. Avoid breathing vapors, mist or gas.			
Storage	Keep away from heat and sources of ignition. Store in original container. Keep containers tightly closed in a dry, cool and well-ventilated place.			
Storage Temperature	Minimum	35 °F / 2 °C	Maximum	120 °F / 49 °C
Storage Conditions	Indoor	X	Outdoor	Heated
				Refrigerated

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Exposure Guidelines

Component	ACGIH TLV	OSHA PEL	NIOSH
Petroleum distillates, hydrotreated light	5 mg/m ³ as oil mist	10 mg/m ³ as oil mist	No data available
Solvent naphtha (petroleum), medium aliphatic	No data available	No data available	No data available
Petroleum distillate	TWA: 100 ppm	TWA: 500 ppm TWA: 2900 mg/m ³	IDLH: 20000 mg/m ³ Ceiling: 1800 mg/m ³ TWA: 350 mg/m ³
Propane	TWA: 1000 ppm	TWA: 1000 ppm TWA: 1800 mg/m ³	IDLH: 2100 ppm TWA: 1000 ppm TWA: 1800 mg/m ³
Mineral oil	TWA: 5 mg/m ³	TWA: 5 mg/m ³	IDLH: 2500 mg/m ³ STEL 10 mg/m ³ TWA: 5 mg/m ³
Butane	STEL: 1000 ppm	No data available	TWA: 800 ppm TWA: 1900 mg/m ³
Nonane	TWA: 200 ppm	No data available	TWA: 200 ppm TWA: 1050 mg/m ³
Barium sulfonate	No data available	No data available	No data available
Paraffin wax	TWA: 2 mg/m ³	No data available	TWA: 2 mg/m ³

Engineering Measures

Ensure adequate ventilation, especially in confined areas. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction.

Personal Protective Equipment

Eye/Face Protection

Safety glasses with side-shields.

Skin Protection

Wear suitable protective clothing, Impervious gloves.

Respiratory Protection

In case of inadequate ventilation wear respiratory protection. When workers are facing concentrations above the exposure limit they must use appropriate certified respirators.

General Hygiene Considerations

Wear protective gloves/clothing. Ensure that eyewash stations and safety showers are close to the workstation location. Remove and wash contaminated clothing before re-use.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical State	Liquid	Viscosity	Non viscous
Color	Amber	Odor	Solvent
Odor Threshold	Not applicable	Appearance	Transparent
pH	Not applicable	Specific Gravity	0.733
Evaporation Rate	21.9 (Butyl acetate=1)	Percent Volatile (Volume)	94.4
VOC Content (%)	93.8	VOC Content (g/L)	687
Vapor Pressure	1257 mmHg @ 70°F	Vapor Density	1.9 (Air = 1.0)
Solubility	Negligible	n-Octanol/Water Partition	No data available
Melting Point/Range	No data available	Decomposition Temperature	No data available
Boiling Point/Range	No data available	Flammability (solid, gas)	No data available
Flash Point	106 °F / 41 °C	Method	Seta closed cup
Autoignition Temperature	No information available.		
Flammability Limits in Air %	.	Upper 9.5 Lower 0.8	

10. STABILITY AND REACTIVITY

Chemical Stability	Stable. Hazardous polymerization does not occur.
Conditions to Avoid	Keep away from open flames, hot surfaces, and sources of ignition
Incompatible Products	Strong oxidizing agents
Hazardous Decomposition Products	Carbon oxides, Sulfur oxides.
Possibility of Hazardous Reactions	None under normal processing

11. TOXICOLOGICAL INFORMATION

Product Information

The following values are calculated based on chapter 3.1 of the GHS document (Rev. 3, 2009):

Oral LD50	No information available
Dermal LD50	No information available
Inhalation LC50	
Gas	No information available
Mist	No information available
Vapor	No information available

Principle Route of Exposure

Eye contact, Skin contact, Inhalation.

Primary Routes of Entry	Inhalation
Acute Effects	
Eyes	Causes eye irritation.
Skin	Causes skin irritation.
Inhalation	Causes respiratory tract irritation. Inhalation may cause central nervous system effects. May cause central nervous system depression. Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness.
Ingestion	Harmful if swallowed. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea. May cause central nervous system depression with nausea, headache, dizziness, vomiting, and incoordination. May be fatal if swallowed and enters airways.
Chronic Toxicity	Prolonged or repeated inhalation may cause damage to the lungs. Prolonged skin contact may defat the skin and produce dermatitis. Liver and kidney injuries may occur.
Target Organ Effects	Central nervous system, Respiratory system, Kidney, Liver, Heart.
Aggravated Medical Conditions	Neurological disorders, Kidney disorders, Liver disorders, Skin disorders, Heart disease.

Component Information

Acute Toxicity

Component	LD50 Oral	LD50 Dermal	LC50 Inhalation	Draize Test	Other
Petroleum distillates, hydrotreated light	> 5000 mg/kg (Rat)	> 2000 mg/kg (Rabbit)	> 5.2 mg/L (Rat) 4 h	no data available	no data available
Solvent naphtha (petroleum), medium aliphatic	> 5000 mg/kg (Rat)	= 3000 mg/kg (Rabbit)	> 5.28 mg/L (Rat) 4 h	no data available	no data available
Petroleum distillate	no data available	no data available	no data available	no data available	no data available
Propane	no data available	no data available	= 658 mg/L (Rat) 4 h	no data available	no data available
Mineral oil	no data available	no data available	= 2062 ppm (Rat) 4 h	no data available	no data available
Butane	no data available	no data available	= 658 g/m ³ (Rat) 4 h	no data available	no data available
Nonane	no data available	no data available	= 3200 ppm (Rat) 4 h	no data available	no data available
Barium sulfonate	no data available	no data available	no data available	no data available	no data available
Paraffin wax	> 3750 mg/kg (Rat)	> 3600 mg/kg (Rabbit)	no data available	no data available	no data available

Chronic Toxicity

Component	Mutagenicity	Sensitization	Developmental Toxicity	Reproductive Toxicity	Target Organ Effects
Petroleum distillates, hydrotreated light	no data available	no data available	no data available	no data available	respiratory system, liver, kidney, CNS
Solvent naphtha (petroleum), medium aliphatic	no data available	no data available	no data available	no data available	CNS, liver, kidneys
Petroleum distillate	no data available	no data available	no data available	no data available	eyes,CNS,respiratory system,skin,kidneys
Propane	no data available	no data available	no data available	no data available	CNS, heart
Mineral oil	no data available	no data available	no data available	no data available	eyes, respiratory system, skin
Butane	no data available	no data available	no data available	no data available	CNS, heart
Nonane	no data available	no data available	no data available	no data available	eyes,CNS,respiratory system,skin
Barium sulfonate	no data available	no data available	no data available	no data available	no data available
Paraffin wax	no data available	no data available	no data available	no data available	eyes, respiratory system, skin

Carcinogenicity

The table below indicates whether each agency has listed any ingredient as a carcinogen.

Component	ACGIH	IARC	NTP	OSHA	Other
Petroleum distillates, hydrotreated light	not applicable	not applicable	not applicable	not applicable	not applicable
Solvent naphtha (petroleum), medium aliphatic	not applicable	not applicable	not applicable	not applicable	not applicable
Petroleum distillate	not applicable	not applicable	not applicable	not applicable	not applicable
Propane	not applicable	not applicable	not applicable	not applicable	not applicable
Mineral oil	not applicable	not applicable	not applicable	not applicable	not applicable
Butane	not applicable	not applicable	not applicable	not applicable	not applicable
Nonane	not applicable	not applicable	not applicable	not applicable	not applicable
Barium sulfonate	not applicable	not applicable	not applicable	not applicable	not applicable
Paraffin wax	not applicable	not applicable	not applicable	not applicable	not applicable

12. ECOLOGICAL INFORMATION

Product Information

No information available.

Component Information

Component	Toxicity to Algae	Toxicity to Fish	Microtox	Water Flea	log Pow
Petroleum distillates, hydrotreated light	no data available	LC50 = 45 mg/L Pimephales promelas 96 h LC50 = 2.2 mg/L Lepomis	no data available	LC50= 4720 mg/L 96 h	N/A

		macrochirus 96 h LC50 = 2.4 mg/L Oncorhynchus mykiss 96 h			
Solvent naphtha (petroleum), medium aliphatic	EC50 = 450 mg/L Pseudokirchneriella subcapitata 96 h	LC50 = 800 mg/L Pimephales promelas 96 h	no data available	EC50> 100 mg/L 48 h	N/A
Petroleum distillate	no data available	no data available	no data available	no data available	N/A
Propane	no data available	no data available	no data available	no data available	2.3
Mineral oil	no data available	no data available	no data available	no data available	N/A
Butane	no data available	no data available	no data available	no data available	2.89
Nonane	no data available	no data available	no data available	no data available	N/A
Barium sulfonate	no data available	no data available	no data available	no data available	N/A
Paraffin wax	no data available	no data available	no data available	no data available	N/A

Persistence and Degradability

No information available.

Bioaccumulation

No information available.

Mobility

No information available.

13. DISPOSAL CONSIDERATIONS

Product Disposal

Dispose of in accordance with local regulations.

Container Disposal

Contents under pressure. Do not puncture. Empty remaining contents. Empty containers should be taken for local recycling, recovery, or waste disposal.

14. TRANSPORT INFORMATION

DOT**Proper Shipping Name**

Consumer commodity

Hazard Class

ORM-D

Description

Consumer commodity ,ORM-D,

TDG**Hazard Class**

2.1

UN-No

UN1950

ICAO**UN-No**

UN1950

Proper Shipping Name

Aerosols

Hazard Class

2.1

Shipping Description

Aerosols,UN1950 LTD. QTY.

IATA**UN-No**

UN1950

Proper Shipping Name

Aerosols, flammable

Hazard Class

2.1

ERG Code

10L

Shipping Description

UN1950,Aerosols, flammable,2.1 LTD. QTY.

IMDG/IMO**Proper Shipping Name**

Aerosols

Hazard Class

2.1

UN-No

UN1950

EmS No.

F-D, S-U

Shipping Description

UN1950, Aerosols,2.1 LIMITED QUANTITIES

15. REGULATORY INFORMATION

Inventories**TSCA**

Complies

DSL

Complies

U.S. Federal Regulations**SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

Component	CAS-No	Weight %	SARA 313 - Threshold Values
Barium sulfonate	61790-48-5	1-5	1.0

SARA 311/312 Hazardous Categorization

Acute Health Hazard	Chronic Health Hazard	Fire Hazard	Sudden Release of Pressure Hazard	Reactive Hazard
Yes	Yes	Yes	Yes	No

CERCLA

Component	Hazardous Substances RQs	CERCLA EHS RQs
Petroleum distillates, hydrotreated light	Not applicable	Not applicable
Solvent naphtha (petroleum), medium aliphatic	Not applicable	Not applicable
Petroleum distillate	Not applicable	Not applicable
Propane	Not applicable	Not applicable
Mineral oil	Not applicable	Not applicable
Butane	Not applicable	Not applicable
Nonane	Not applicable	Not applicable
Barium sulfonate	Not applicable	Not applicable
Paraffin wax	Not applicable	Not applicable

16. OTHER INFORMATION

Prepared By Angela Hutson
Supersedes Date 07/21/2010
Issuing Date 08/01/2013
Reason for Revision No information available.
Glossary No information available.
List of References. No information available.

CHEMSEARCH DIV. OF NCH CORP. assumes no responsibility for personal injury or property damage caused by the use, storage, or disposal of the product in a manner not recommended on the product label. Users assume all risks associated with such unrecommended use, storage or disposal of the product. The information provided on this MSDS is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guide for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered as a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other material or in any process, unless specified in the text.