

Safety Data Sheet

OSHA Hazard Communication Standard 29 CFR 1910.1200. Prepared to GHS Rev 3.

Revision date: Initial version

Date of issue: Feb.10, 2015

Product name:	AW Hydraulic Oil ISO 46
----------------------	-------------------------

SECTION 1: Identification

Product identifier: AW Hydraulic Oil ISO 46.
Synonyms: Standard Hydraulic Oil.
Product Code Number: 9616, 9636, 9637, 9638.
SDS number: CGF001
Recommended use: Standard Hydraulic Oil.
Recommended restrictions: None known.

Manufacturer/Importer/Supplier/Distributor information:

Company Name: SPX Hydraulic Technologies.
Company Address: 5885 11th Street
Rockford, IL 61109
Company Telephone: Office hours (Mon – Fri)
8.00am – 5:00pm (CST)
(815) 874-5556
Company Contact Name: EH&S Department.
Emergency phone number: INFOTRAC 24 Hour Emergency Numbers:
USA, Canada, Puerto Rico (800) 535-5053.
International (352) 323-3500.

SECTION 2: Hazard(s) identification

Classification of the chemical in accordance with paragraph (d) of §1910.1200:

Physical hazards

No physical hazards for this product.

Health hazards

Aspiration Hazard, Category 1.

Environmental hazards

No environmental hazards for this product.

GHS Signal word: DANGER.

GHS Hazard statement(s): May be fatal if swallowed and enters airways.

GHS Hazard symbol(s):



GHS Precautionary statement(s):

Prevention:	No prevention precautionary phrases.
Response:	If swallowed: Immediately call a poison center/doctor/physician. Do NOT induce vomiting.
Storage:	Store locked up.
Disposal:	Dispose of contents/containers to an appropriate treatment and disposal facility in accordance with applicable laws and regulations.

Hazard(s) not otherwise Classified (HNOC):	None known.
---	-------------

Percentage of ingredient(s) of unknown acute toxicity:

96% of the mixture consists of ingredients of unknown acute toxicity (oral/dermal/inhalation).

SECTION 3: Composition/information on ingredients

Mixture:

Chemical name	Concentration (weight %)	CAS#
Distillates (petroleum), solvent- dewaxed heavy paraffinic	0-95 %	64742-65-0
Distillates (petroleum), hydro treated - heavy paraffinic	0-60%	64742-54-7
Paraffin oils (petroleum), catalytic - dewaxed light	0-60%	64742-71-8
Additive	<1 %	Proprietary

The specific chemical identity and/or exact percentage (concentration) of composition has been withheld as a trade secret due to the proprietary nature of one of the components.

SECTION 4: First-aid Measures

Inhalation: Move to fresh air. Treat symptomatically. See Section 8 for additional measures to reduce or eliminate exposure. If symptoms persist, seek medical attention.

Skin contact: Wash area of contact thoroughly with soap and water. If symptoms persist, seek medical attention.

Eye contact: If eyes become irritated, flush immediately with copious amounts of lukewarm water for at least 15 minutes. If easy to do, remove contact lenses. Get medical attention if irritation persists.

Ingestion: DO NOT induce vomiting. Consult a physician if necessary.

Most important symptoms/effects, acute and delayed: If material enters lungs, signs and symptoms may include coughing, choking, wheezing, difficulty in breathing, chest congestion, shortness of breath, and/or fever. The onset of respiratory symptoms may be delayed for several hours after exposure. Ingestion may result in nausea, vomiting and/or diarrhea.

Indication of immediate medical attention and special treatment needed: None known

SECTION 5: Fire-fighting measures

Suitable extinguishing media: Water spray, Carbon dioxide, Dry chemical, Alcohol foam

Unsuitable extinguishing media: Do not use water jet.

Specific hazards arising from the chemical: Hazardous combustion products may include carbon monoxide and other toxic gases/vapors.

Special protective equipment and precautions for fire-fighters: Self-contained breathing apparatus and full protective clothing must be worn in case of fire. Fight fire from a protected location. Water may be ineffective in fighting the fire. Use water spray to keep fire-exposed container cool.

SECTION 6: Accidental release measures

Personal precautions, protective equipment and emergency procedures:

Wear appropriate personal protective equipment (see Section 8). Do not breathe fumes or vapor.

Methods and materials for containment and cleaning up:

Eliminate sources of ignition. Stop source of leak if safe. Prevent entry into waterways and sewer systems. Absorb in vermiculite, dry sand or earth. Sweep up and place in a clearly labeled container for chemical waste.

SECTION 7: Handling and Storage

Precautions for safe handling: Avoid breathing mist or vapors. Avoid contact with eyes. Use only with adequate ventilation. Wash thoroughly after handling. Observe good personal hygiene practices. Change protective gloves/clothing when signs of contamination appear. Keep out of reach of children.

Conditions for safe storage, including any incompatibles: Store in original factory container in a dry area. Do not transfer to an unmarked container. Keep container tightly closed and in a well-ventilated place. Store away from heat and light.

SECTION 8: Exposure controls/personal protection

Control Parameters:

Occupational exposure limits:

US OSHA HAZARDOUS COMPONENTS (29 CFR 1910.1200): Permissible Exposure Limits		
Substance	PEL-TWA (8 hour)	PEL-STEL (15 min)
Oil mist, mineral	5 mg/m ³	No data available
Distillates (petroleum), hydro treated - heavy paraffinic	No data available	No data available
Paraffin oils (petroleum), catalytic - dewaxed light	No data available	No data available
Additive	No data available	No data available

US ACGIH Threshold Limit Values		
Substance	TLV-TWA (8 hour)	TLV-STEL (15 min)
Oil mist, mineral	5 mg/m ³	No data available
Distillates (petroleum), hydro treated - heavy paraffinic	No data available	No data available
Paraffin oils (petroleum), catalytic - dewaxed light	No data available	No data available
Additive	No data available	No data available

US NIOSH Guidelines		
Substance	REL (10 hour)	STEL
Oil mist, mineral	5 mg/m ³	10 mg/m ³
Distillates (petroleum), hydro treated - heavy paraffinic	No data available	No data available
Paraffin oils (petroleum), catalytic - dewaxed light	No data available	No data available
Additive	No data available	No data available

Appropriate engineering controls: Maintain air concentrations below occupational exposure standards using engineering controls if necessary. Local exhaust ventilation is recommended. Eye wash station and showers required for emergency use.

Individual protection measures, such as personal protective equipment:

Eye/face protection: Wear safety glasses or full face shield if splashes are likely to

occur Approved to the appropriate OSHA standard. If possible, have eye-washing facilities readily available where eye irritation can occur.

Skin and Hand protection: Skin protection is not required under normal conditions of use. Where hand contact with the product may occur the use of gloves approved to relevant standards (e.g.US: F739) made from the following materials may provide suitable chemical protection: PVC, neoprene or nitrile rubber gloves. Suitability and durability of a glove is dependent on usage, e.g. frequency and duration of contact, chemical resistance of glove material, glove thickness, dexterity. Always seek advice from glove suppliers.

Contaminated gloves should be replaced. Personal hygiene is a key element of effective hand care. Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly. Application of a non-perfumed moisturizer is recommended.

Respiratory protection: No respiratory protection is ordinarily required under normal conditions of use. In accordance with good industrial hygiene practices, precautions should be taken to avoid breathing of material. If engineering controls do not maintain airborne concentrations to a level which is adequate to protect worker health, select respiratory protection equipment suitable for the specific conditions of use and meeting relevant legislation. Check with respiratory protective equipment suppliers. Where air-filtering respirators are suitable, select an appropriate combination of mask and filter pursuant to the requirements of OSHA Standards 29 CFR 1910.134 and 29 CFR 1926.103.

Other: Use as necessary to prevent exposure. Work clothing should be changed daily. Contaminated clothing should be removed and washed thoroughly before re-using.

Thermal hazards: No data available.

SECTION 9: Physical and chemical properties

Appearance

Physical state:

Liquid

Form:

Liquid

Color:

Blue

Odor:

Mild

Odor threshold:

Not available

pH:

Not available

Melting point/freezing point:

Not available

Boiling point:

Not available

Flash point:

>380 °F

Evaporation rate:

Not available

Flammability (solid, gas):

Not available

Upper/lower flammability or explosive limits

Flammability limit – lower (%):

Not available

Flammability limit – upper(%):

Not available

Explosive limit – lower (%):

Not available

Explosive limit – upper (%):

Not available

Vapor pressure:

Not available

Vapor density:	Not available
Specific gravity:	0.87 -0.89
Relative density temperature:	Not available
Solubility in water:	Insoluble
Partition coefficient (n-octanol/water):	Not available.
Auto-ignition temperature:	Not available
Decomposition temperature:	Not available
Viscosity:	46 cSt @40 degrees C
Viscosity temperature:	Not available

Other information

Bulk density:	Not available
Flash point class:	Not available
VOC (Weight %):	Not available

SECTION 10: Stability and Reactivity

Reactivity:	None known
Chemical stability:	Stable
Possibility of hazardous reactions:	None known
Conditions to avoid:	Heat, sparks, flames.
Incompatible materials:	Strong oxidizing agents.
Hazardous decomposition Products:	Carbon monoxide, Carbon dioxide

SECTION 11: Toxicological information

Information on likely routes of exposure:

Inhalation:	None known
Ingestion:	None known
Skin:	Skin is a primary route of exposure.
Eye:	The eyes are a primary route of exposure.

Symptoms related to the physical, chemical, and toxicological characteristics:

None known.

Delayed and immediate effects and chronic effects from short or long-term exposure:

None known.

Acute toxicity:

Ingredient Information:

Substance	Test Type (species)	Value
Distillates (petroleum), solvent- dewaxed heavy paraffinic	LD ₅₀ Oral (Rat)	>5000 mg/kg
	LD ₅₀ Dermal (Rabbit)	>5000 mg/kg
	LC ₅₀ Inhalation (Rat)	>5 mg/l (4h)

Distillates (petroleum), hydro treated - heavy paraffinic	LD ₅₀ Oral (Rat)	>5000 mg/kg
	LD ₅₀ Dermal (Rabbit)	>5000 mg/kg
	LC ₅₀ Inhalation (Rat)	> 4 mg/l (4h)
Paraffin oils (petroleum), catalytic - dewaxed light	LD ₅₀ Oral (Rat)	>5000 mg/kg
	LD ₅₀ Dermal (Rabbit)	>2000 mg/kg
	LC ₅₀ Inhalation (Rat)	2.18 mg/L air (4h)
Additive	LD ₅₀ Oral (Rat)	No data available
	LD ₅₀ Dermal (Rabbit)	No data available
	LC ₅₀ Inhalation (Rat)	No data available

Product Acute Toxicity Estimates:

Acute Oral Toxicity (rat)

Product: >5000 mg/kg (estimate based on components)

Acute Dermal Toxicity (rabbit)

Product: No data available

Acute Inhalation Toxicity

Product: No data available.

Skin corrosion/irritation:

Based upon information available on the known components, the product is not expected to cause skin corrosion or irritation.

Serious eye damage/eye irritation:

Based upon information available on the known components, the product is not expected to cause eye damage or eye irritation.

Respiratory sensitization:

Based upon information available on the known components, the product is not expected to cause respiratory sensitization.

Skin sensitization:

Based upon information available on the known components, the product is not expected to cause skin sensitization.

Germ cell mutagenicity:

Based upon information available on the known components, the product is not anticipated to be a mutagen.

Carcinogenicity:

Based upon information available on the known components, the product is not anticipated to be a carcinogen.

Reproductive toxicity:

Based upon information available on the known components, the product is not anticipated to cause reproductive toxicity.

**Specific target organ toxicity-
Single exposure:**

Based upon information available on the known components, the product is not anticipated to cause specific target organ toxicity after single exposure.

**Specific target organ toxicity-
Repeat exposure:**

Based upon information available on the known components, the product is not anticipated to cause specific target organ toxicity after repeated or prolonged exposure.

Aspiration hazard:

Based upon information available the component, Distillates (petroleum), solvent-dewaxed heavy paraffinic causes aspiration into the lungs when swallowed or vomited may cause pneumonitis which can be fatal. Therefore the product is anticipated to be an aspiration hazard.

Further information: No data available

SECTION 12: Ecological information

Ecotoxicity:

Product data:

No data available

Ingredient Information:

Substance	Test Type	Species	Value
Distillates (petroleum), solvent- dewaxed heavy paraffinic	LL/EL/IL50 NOEC/NOEL	Fish	Practically non toxic: LL/EL/IL50 > 100 mg/l NOEC/NOEL > 100 mg/l (based on test data)
	LL/EL/IL50 NOEC/NOEL	Invertebrate	Practically non toxic: LL/EL/IL50 > 100 mg/l NOEC/NOEL expected to be > 1.0 - <= 10 mg/l (based on test data)
	LL/EL/IL50	Algae	Practically non toxic: LL/EL/IL50 > 100 mg/l
Distillates (petroleum), hydro treated - heavy paraffinic	NOEC	Fish Pimephales promelas	NOEC--> 1000 mg/l (7d)
	NOEC	Invertebrate Daphnia magna	NOEC--> 1000 mg/l (21d)
	EC50	Algae	EC50--> 1000 mg/l (96h)

Paraffin oils (petroleum), catalytic - dewaxed light	NOELR LL50	Fish	NOELR >= 1000 mg/L (14d) LL50 > 100 mg/L (96h)
	NOEL LL50	Invertebrate	NOEL 10mg/L (21d) LL50 > 10000 mg/L (24h)
	NOEL	Algae	NOEL >= 100 mg/L (72h)
Additive	LC ₅₀	Fish	No data available
	EC ₅₀	Invertebrate	No data available
	LC ₅₀	Algae	No data available

Persistence and degradability: Major constituents are expected to be readily biodegradable, but the product contains components that may persist in the environment.

Bioaccumulative potential: Contains components with the potential to bioaccumulate.

Mobility in soil: If it enters soil, it will adsorb to soil particles and will not be mobile.

Mobility in general: Liquid under most environmental conditions. Floats on water.

Other adverse effects: An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.

SECTION 13: Disposal considerations

Disposal instructions:

Recover or recycle if possible. It is the responsibility of the waste generator to determine the toxicity and physical properties of the material generated to determine the proper waste classification and disposal methods in compliance with all applicable Federal, State and local regulations. Do not dispose into the environment, in drains or in water courses.

SECTION 14: Transport Information

Land Transport DOT: Not regulated.

Air Transport IATA: Not regulated.

Sea Transport IMDG: Not regulated.

SECTION 15: Regulatory Information

USA:

United States Federal Regulations: This SDS complies with the OSHA, 29 CFR 1910.1200. The product is hazardous under OSHA.

Toxic Substances Control Act (TSCA) – All substances in this product are listed, as required, on the TSCA inventory.

SARA Superfund and Reauthorization Act of 1986 Title III sections 302, 311,312 and 313:

Section 302 – No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

CERCLA Hazardous Substance List, 40 CFR 302.4: This product contains chemicals listed on CERCLA. Zinc Compounds (<1 %)

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130):
None

Clean Water Act Section 311 Hazardous Substances (40 CFR 117.3): None

SARA Title III

Section 302 Extremely Hazardous Substance (40 CFR 355, Appendix A): None

Section 311/312 (40 CFR 370):

Immediate Hazard: Yes

Delayed Hazard: No

Fire Hazard: No

Pressure Hazard: No

Reactivity Hazard: No

Section 313 Toxic Release Inventory (40 CFR 372):

None

STATE REGULATIONS:

This SDS contains specific health and safety data is applicable for state requirements. For details on your regulatory requirements you should contact the appropriate agency in your state.

California Proposition 65 (California Safe Drinking Water and Toxic Enforcement Act of 1986): Impurities: <1 ppm cadmium, <1 ppm lead, <2 ppm arsenic.

Massachusetts Right to Know: Oil Mist, mineral; Petroleum paraffin oils, catalytic dewaxed light are listed on the Massachusetts Right to Know list.

Minnesota Hazardous Substance List: None of the components are listed on the Minnesota HSL.

New Jersey Right to Know: None of the components are listed on the New Jersey Right to Know list.

Pennsylvania Right to Know: None of the components are listed on the Pennsylvania Right to Know list.

SECTION 16: Other Information

Revision Date: February 10, 2015

To the best of our knowledge, the information contained herein is accurate. However SPX Hydraulic Technologies does not assume any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards which exist.