



SAFETY DATA SHEET

Revision date 22-Jul-2017

Version 10

Supersedes Date: 10-Jul-2017

Section 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

Product identifier

Product Code 24030.G01

Product Name DURAGLAS GAL

Other means of identification

No information available

Recommended use of the chemical and restrictions on use

Fillers and putty

Details of the supplier of the safety data sheet

See section 16 for more information

The Valspar Corporation
PO Box 1461
Minneapolis, MN 55440

E-mail address msds@valspar.com

Emergency telephone number

United States of America 1-888-345-5732
American Samoa, Guam, Northern Mariana Islands, Puerto Rico, U.S. Virgin Islands 1-800-255-3924

Section 2: HAZARDS IDENTIFICATION

Classification

Skin corrosion/irritation	Category 2
Serious eye damage/eye irritation	Category 2
Carcinogenicity	Category 1B
Reproductive toxicity	Category 2
Specific target organ toxicity (repeated exposure)	Category 1
Flammable solids	Category 1

Label elements



Signal word

DANGER

HAZARD STATEMENTS

Flammable solids
Causes skin irritation
Causes serious eye irritation
May cause cancer
Suspected of damaging fertility or the unborn child
Causes damage to the following organs through prolonged or repeated exposure: Ears

PREVENTION

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves/protective clothing/eye protection/face protection. Wash face, hands and any exposed skin thoroughly after handling. Do not breathe dust/fume/gas/mist/vapors/spray. Do not eat, drink or smoke when using this product. P210 - Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Ground/bond container and receiving equipment. Use explosion-proof electrical/ ventilating/ lighting/ equipment.

RESPONSE

IF exposed or concerned: Get medical advice/attention.

Eyes

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

Skin

IF ON SKIN: Wash with plenty of soap and water. If skin irritation occurs: Get medical advice/attention. Take off contaminated clothing and wash before reuse.

Inhalation

IF INHALED: Call a POISON CENTER or doctor if you feel unwell.

Ingestion

Do NOT induce vomiting. IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell.

Fire

In case of fire: Use CO₂, dry chemical, or foam for extinction.

STORAGE

Store locked up.

DISPOSAL

Dispose of contents/containers in accordance with local regulations.

HAZARDS NOT OTHERWISE CLASSIFIED (HNOC)

No information available.

OTHER HAZARDS

Not applicable.

UNKNOWN ACUTE TOXICITY

.0001% of the mixture consists of ingredient(s) of unknown toxicity.

Section 3: COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS No	weight-%
Styrene	100-42-5	10 - 25
N,N-Dimethylaniline	121-69-7	0.1 - 0.3

*The exact percentage (concentration) of composition has been withheld as a trade secret.

Section 4: FIRST AID MEASURES

First Aid Measures

General advice

IF exposed or concerned: Get medical advice/attention.

Eye contact

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

Skin Contact

IF ON SKIN: Wash with plenty of soap and water. If skin irritation occurs: Get medical advice/attention. Take off contaminated clothing and wash before reuse.

Inhalation

IF INHALED: Call a POISON CENTER or doctor if you feel unwell.

Ingestion

Do NOT induce vomiting. IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell.

Most important symptoms and effects, both acute and delayed

Symptoms No information available.

Indication of any immediate medical attention and special treatment needed

Note to physicians Treat symptomatically.

Section 5: FIRE FIGHTING MEASURES

Suitable extinguishing media

Dry chemical, CO2, water spray or alcohol-resistant foam.

Not to be used for safety reasons: Strong water jet

Specific hazards arising from the chemical

Burning produces heavy smoke. Fire may produce irritating and/or toxic gases. In the event of fire and/or explosion do not breathe fumes.

Special protective equipment for fire-fighters

Wear self-contained breathing apparatus and protective suit. Cool containers with flooding quantities of water until well after fire is out. Do not allow run-off from fire-fighting to enter drains or water courses.

Section 6: ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal precautions

Avoid breathing vapors or mists. Use personal protective equipment as required. Avoid contact with skin, eyes or clothing. Keep people away from and upwind of spill/leak. Remove all sources of ignition.

For emergency responders

Use personal protection recommended in Section 8.

Environmental precautions

Do not allow into any sewer, on the ground or into any body of water. If the product contaminates lakes, rivers or sewage, inform appropriate authorities in accordance with local regulations.

Methods and material for containment and cleaning up

Methods for containment

Prevent further leakage or spillage if safe to do so.

Methods for cleaning up

Dispose of waste product or used containers according to local regulations. Clean with detergents. Avoid solvent cleaners. Pick up and transfer to properly labeled containers. Contain and collect spillage with an electrically protected vacuum cleaner or by wet-brushing and place in container for disposal according to local regulations (see section 13).

Section 7: HANDLING AND STORAGE

Precautions for safe handling

Advice on safe handling

Use personal protection recommended in Section 8. Never use pressure to empty container. Comply with the health and safety at work laws. Prevent product from entering drains. Do not breathe dust/fume/gas/mist/vapors/spray. Use only in well-ventilated areas. Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity). Use spark-proof tools and explosion-proof equipment. All equipment used when handling the product must be grounded.

General Hygiene Considerations

Avoid contact with skin, eyes or clothing. When using do not eat, drink or smoke. Wash contaminated clothing before reuse.

Conditions for safe storage, including any incompatibilities

Storage Conditions

Keep/store only in original container. Store in accordance with local regulations. Keep unauthorized personnel away. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Keep tightly closed in a dry and cool place.

Incompatible materials

Bases. Strong oxidizing agents. Acids. Alkali. Aluminum. Copper. Halogens.

Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Exposure Limits

If S* appears in the OEL table, it indicates this chemical contains a skin notation.

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Styrene 100-42-5	STEL: 40 ppm TWA: 20 ppm	TWA: 100 ppm Ceiling: 200 ppm	IDLH: 700 ppm TWA: 50 ppm TWA: 215 mg/m ³ STEL: 100 ppm STEL: 425 mg/m ³
N,N-Dimethylaniline 121-69-7	STEL: 10 ppm TWA: 5 ppm S*	TWA: 5 ppm TWA: 25 mg/m ³ S*	IDLH: 100 ppm TWA: 5 ppm TWA: 25 mg/m ³ STEL: 10 ppm STEL: 50 mg/m ³

Appropriate engineering controls

Engineering Controls

Ensure adequate ventilation, especially in confined areas. Provide local exhaust ventilation. In case of insufficient ventilation, wear suitable respiratory equipment.

Individual protection measures, such as personal protective equipment

Eye/face protection

Wear safety glasses with side shields (or goggles).

Skin and body protection

Wear suitable protective clothing.

Hand Protection

There is no one glove material or combination of materials that will give unlimited resistance to any individual or combination of chemicals. Ensure that the breakthrough time of the glove material is not exceeded. Refer to glove supplier for information on breakthrough time for specific gloves. The instructions and information provided by the glove manufacturer on use, storage, maintenance and replacement must be followed. Gloves should be replaced regularly and if there is any sign of damage to the glove material. Always ensure that gloves are free from defects and that they are stored and used correctly. The performance or effectiveness of the glove may be reduced by physical / chemical damage and poor maintenance. Wear protective gloves.

Respiratory protection

When workers are facing concentrations above the exposure limit they must use appropriate certified respirators.

Thermal Protection

No information available

Section 9: PHYSICAL AND CHEMICAL PROPERTIES**Information on basic physical and chemical properties**

Physical state	Solid
Appearance	No information available
Odor	Aromatic
Color	dark green
Odor Threshold	No information available
pH value	No information available
Melting point/freezing point	No information available
Boiling point / boiling range	No information available °C / °F
flash point	29 °C / 84 °F
evaporation rate	No information available
Flammability (solid, gas)	No information available
Flammability Limit in Air	
Upper flammability limit:	No information available
Lower flammability limit:	No information available
Vapor Pressure	No information available
vapor density	No information available
Density (lbs per US gallon)	14.22
specific gravity	1.7
Solubility(ies)	No information available
Partition coefficient	No information available
Autoignition temperature	No information available
Decomposition temperature	No information available
Kinematic viscosity	52941 mm ² per second
Dynamic viscosity	No information available

Other information**Section 10: STABILITY AND REACTIVITY**

Reactivity	No information available.
Chemical stability	Stable under normal conditions.
Possibility of Hazardous Reactions	None under normal processing.
Hazardous polymerization	None under normal processing.
Conditions to avoid	Heat, flames and sparks.
Incompatible materials	Bases. Strong oxidizing agents. Acids. Alkali. Aluminum. Copper. Halogens.
Hazardous Decomposition Products	Carbon monoxide. Carbon dioxide (CO ₂). Nitrogen oxides (NO _x). Hydrocarbons.

Section 11: TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Eye contact

Causes serious eye irritation

Skin Contact

Causes skin irritation

Ingestion

Not applicable

Inhalation

Not applicable

Numerical measures of toxicity - Component Information

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
Styrene 100-42-5	= 1000 mg/kg (Rat)	-	= 11.7 mg/L (Rat) 4 h
N,N-Dimethylaniline 121-69-7	= 951 mg/kg (Rat)	= 1770 µL/kg (Rabbit)	> 0.5 - 5.0 mg/L (Rat) 4 h

Numerical measures of toxicity - Product Information

The following values are calculated based on chapter 3.1 of the GHS document .

ATEmix (oral) 19456 Mg/kg

ATEmix (dermal) 58367 Mg/kg

ATEmix (inhalation-dust/mist) 10.2 mg/l

ATEmix (inhalation-vapor) 73 mg/l

UNKNOWN ACUTE TOXICITY .0001% of the mixture consists of ingredient(s) of unknown toxicity.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Chemical Name	ACGIH	IARC	NTP	OSHA
Styrene 100-42-5		Group 2B	Reasonably Anticipated	X

IARC (International Agency for Research on Cancer)

Group 2B - Possibly Carcinogenic to Humans.

NTP (National Toxicology Program)

Reasonably Anticipated - Reasonably Anticipated to be a Human Carcinogen.

OSHA (Occupational Safety and Health Administration of the US Department of Labor)

X - Present.

Skin corrosion/irritation Causes skin irritation

Serious eye damage/eye irritation Causes serious eye irritation

Skin sensitization Not applicable

Respiratory sensitization Not applicable

Germ cell mutagenicity Not applicable

Carcinogenicity May cause cancer

Reproductive Toxicity Suspected of damaging fertility or the unborn child

Specific target organ toxicity (single exposure) Not applicable

Specific target organ toxicity (repeated exposure)

Causes damage to the following organs through prolonged or repeated exposure: Ears

Aspiration hazard Not applicable

Section 12: ECOLOGICAL INFORMATION

Ecotoxicity

Environmental precautions

Prevent product from entering drains.

Persistence and degradability

No information available

Bioaccumulation

No information available

Mobility

No information available

Other adverse effects

No information available

Section 13: DISPOSAL CONSIDERATIONS**Waste treatment methods****Disposal of wastes**

Disposal should be in accordance with applicable regional, national and local laws and regulations.

Contaminated packaging

Improper disposal or reuse of this container may be dangerous and illegal. Empty containers must be scrapped or reconditioned.

Section 14: TRANSPORT INFORMATION

	DOT	IMDG	IATA
14.1 UN/ID no	UN3175	UN3175	UN3175
14.2 Proper shipping name	Solids containing flammable liquid, n.o.s Styrene	Solids containing flammable liquid, n.o.s Styrene	Solids containing flammable liquid, n.o.s Styrene
14.3 Hazard Class	4.1	4.1	4.1
14.4 Packing Group	II	II	II
14.5 Environmental hazard	Not applicable		
14.6 Special Provisions	47, IB6, IP2, T3, TP33 Emergency Response Guide Number 133	216, 274 EmS-No F-A, S-I	A46
14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code			No information available

The supplier may apply one of the following exceptions: Combustible Liquid (49 CFR 173.150(f)); Consumer Commodity (49 CFR 173.150(c), ICAO/IATA SP A112); Limited Quantity (49 CFR 173.150(b), ICAO Part 3 Chapter 4, IATA 2.7, IMDG Chapter 3.4); Viscous Liquid (49 CFR 173.121(b), IMDG 2.3.2.2, IATA 3.3.3.1.1, ICAO 3.2.2, ADR 2.2.3.1.5); Does Not Sustain Combustion (49 CFR 173.120(a), IATA 3.3.1.3, ICAO 3.1.3, IMDG 2.3.1.3, ADR 2.2.3.1.1 Note 1); or others as allowed under hazardous materials/dangerous goods regulations.

Section 15: REGULATORY INFORMATION**International Inventories**

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

All components are listed or exempt from listing.

DSL - Canadian Domestic Substances List

Not all components are listed or exempt from listing

US Federal Regulations

Chemical Name	SARA 313 - Threshold Values %	Metals	Hazardous air pollutants (HAPs) content
Styrene 100-42-5 10 - 25	0.1		Present
N,N-Dimethylaniline 121-69-7 0.1 - 0.3	1		Present

SARA 311/312 Hazard Categories

Acute health hazard	Yes
Chronic Health Hazard	Yes
Fire hazard	Yes
Sudden release of pressure hazard	No
Reactive Hazard	Yes

Chemical Name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
Styrene 100-42-5	1000 lb			X

Chemical Name	Hazardous Substances RQs	CERCLA/SARA RQ	Reportable Quantity (RQ)
Styrene 100-42-5	1000 lb		RQ 1000 lb final RQ RQ 454 kg final RQ
N,N-Dimethylaniline 121-69-7	100 lb		RQ 100 lb final RQ RQ 45.4 kg final RQ

US State Regulations

Rule 66 status of product

Not photochemically reactive.

California Proposition 65

WARNING! This product contains chemical(s) known to the State of California to cause cancer and/or to cause birth defects or other reproductive harm.

U.S. EPA Label information

EPA Pesticide registration number Not applicable

U.S. State Right-to-Know Regulations

Chemical Name
Proprietary Inert
Proprietary Non-Hazardous Ingredient - Proprietary CAS
Magnesium carbonate 546-93-0
Styrene 100-42-5
Proprietary Non-Hazardous Ingredient - Proprietary CAS
Inorganic Inert
Limestone 1317-65-3
N,N-Dimethylaniline 121-69-7

Section 16: OTHER INFORMATION

HMIS

Health hazards 3*
 * = Chronic Health Hazard

Flammability 3

Physical hazards 1

Personal Protection X

Supplier Address

Valspar Coatings
701 Shiloh Rd.
Garland, TX 75042
972-276-5181

Prepared By Product Stewardship

Revision date 22-Jul-2017

Revision Note No information available

Disclaimer

The information on this Safety Data Sheet (SDS) is based on the present state of our knowledge, current national legislation and guidelines. As the specific conditions of use of the product are outside the supplier's knowledge and control the user is responsible for ensuring that the requirements of relevant legislation are complied with. This SDS should not be construed as any guarantee of the technical performance or suitability for particular applications. UNLESS SUPPLIER AGREES OTHERWISE IN WRITING, SUPPLIER MAKES NO WARRANTIES, EXPRESS OR IMPLIED, AND DISCLAIMS ALL IMPLIED WARRANTIES INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR USE OR FREEDOM FROM PATENT INFRINGEMENT. SUPPLIER WILL NOT BE LIABLE FOR ANY SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES.

End of Safety Data Sheet